

Floor Saw FS-500P

Applications:

- Cutting plain concrete, reinforced concrete and asphalt road surfaces

Features:

- Accommodates 250mm – 500mm diameter blades
- Heavy-duty, removable plastic water tank with 48 litre capacity
- Walk-behind
- Manual lifting screw system for adjusting cutting depth
- Accurate cut-depth control within 0.5mm with position lock
- Robust adjustable follower arm
- Blade cooling system
- Fully adjustable handles for operator comfort
- Quick-remove blade guard for efficient blade changes
- Anti-vibration rubber tool sleeve
- High-strength construction with full welded housing for demanding working environments
- Robust structure to withstand vibration and continuous, heavy use
- High durability plastic V-belt safety guard
- Heavy-duty bearings and components
- 4 X V-Belt Drive System with adjustable tensioning system
- Lifting Frame for ease of loading/unloading
- Water tank fitted with flow valve for blade cooling, mesh opening for filling and drain plug
- Designed for easy maintenance
- Spare parts for all components locally available



Specifications	<ul style="list-style-type: none">• 48 litre water tank• Accommodates 250mm to 500mm diameter blades with 25.4 mm ID• 195mm maximum cut depth with 500mm blade• 30 mm diameter Blade Shaft• 3,000 – 3,600 rpm blade speed
Drive System	<ul style="list-style-type: none">• Honda GX390QX• 13hp (9.6kW) 4-stroke, OHC petrol – pull-start• 6.5 litre fuel tank capacity (3.7 liter/hour consumption)• 4 X V-Belt Drive System with adjustable tensioning system• Classic V-Belt (SPA-VB13X920F)
Dimensions	Width 0.55m Length 1.06m Height 1.08m (with 500mm blade installed) Weight 140 kg

Note: Specifications may be changed without notice

