

Floor Grinder FG-250SE

Applications:

- Grinding concrete
- Repairing damaged concrete slabs
- Removing urethanes or epoxy thin-coats
- Leveling high spots or surface imperfections
- Smoothing rough surfaces, rain marks or trowel marks
- Removing paint build-ups, resins and more
- Garage Floors
- Pre Coating Preparation
- Coating Removal
- Concrete Polishing
- Industrial Floor Resurfacing

Features:

- The self-levelling swivel head and proprietary coupler ensure perfect alignment between the grinding disk and the surface, extending the life of the grinding disk
- Adjustable handle for different heights
- Coupler ensures perfect alignment for efficient and even grinding
- Exhaust port for dust extraction
- Floating skirt for efficient dust containment
- Control switch is situated within easy reach of the operator
- Deadman cut-off switch
- Robust design
- Connection for vacuum port
- Warranty – 1 year on motor and (1 year or 400 000 starts) on Electrical starter box
- All spare parts locally available



Capacity	<ul style="list-style-type: none">• 250 mm (10") Diamond blocked grinding disk
Drive System	<ul style="list-style-type: none">• 2.2.kW• 220 V single phase 50Hz• 1400 RPM, 14 Amp
Dimensions	Width 0.45m (17") Length 1.15m (45") Height 0.90m Weight: ±43 kg (94 lbs.) Min. working distance from wall: 30 mm

Note: Specifications may be changed without notice



www.y-force.com



www.y-force.com

www.y-force.com